

Foam Pneumatic

210-250 LBS capacity

WHEELS

FEATURES



ALGOOD

BALL BEARINGS: Ball
TEMPERATURE: -20°F to 130°F
FINISH: Plastic Grey Hub
DESCRIPTION: Foam Pneumatic wheels are excellent for applications where floor and equipment protection is vital. The foam fill provides for shock absorption, quiet operation and ease of rolling. Excellent for delicate materials and uneven and rough floor surfaces. For manual operation only.

EXCELLENT FOR

- Uneven floors such as agricultural, institutional & industrial
- Shock absorbing uses for indoor & outdoor rough terrain



PNEUMATIC FOAM



PNEUMATIC FOAM GREY

HUB SIZE

HUB LENGTH	CODE#
2"	A
2 1/4"	B
2 1/2"	C
2 5/8"	D
3"	E
3 1/4"	I
4"	F
4 1/4"	H

WHEEL

PART NUMBER

Diameter	Tread Width	Capacity Lbs.	Hub Length	Hub Type	Tire Colour	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
6"	2"	210	2 1/2"	Center	Black	1/2"	5/8" * 3/4"	Ball	W-7006-PFCC-BB	0.79
		210	2 1/2"	Center	Grey	1/2"	5/8" * 3/4"	Ball	W-7006-PFCCG-BB	0.79
8"	2 1/2"	235	3"	Center	Black	1/2"	5/8" * 3/4"	Ball	W-7908-PFCE-BB	1.70
		235	3"	Center	Grey	1/2"	5/8" * 3/4"	Ball	W-7908-PFCEG-BB	1.70
10"	3"	250	2 1/4"	Offset	Black	5/8"	--	Ball	W-7910-PFOB	2.10
		250	2 1/4"	Offset	Black	5/8"	1/2" * 3/4"	Ball	W-7910-PFOB-BB	2.51
		250	4"	Center	Black	1/2"	5/8" * 3/4"	Ball	W-7910-PFCF-BB	2.52
		250	4"	Center	Grey	1/2"	5/8" * 3/4"	Ball	W-7910-PFCFG-BB	2.52