

Hard Rubber

100-275 LBS
capacity

WHEELS

FEATURES



ALGOOD

BEARINGS: Nylon, Steel
TEMPERATURE: -45°F to 160°F
COLOURS: Black, Grey
DESCRIPTION: This Solid Hard Rubber wheel is used for higher load capacities than soft rubber. Good floor protection and easier mobility. Will not develop flat spots under standing loads. High resistance to oil, grease and mild or diluted acids.
DUROMETER: 70-80 D Scale

EXCELLENT FOR

- Economical
- Resistant to most chemicals
- Rejects floor debris
- Small waste bins
- Factory use
- Textile carts
- Abusive applications

OPTIONS

- TG Thread Guards
(1900 series wheels only)

SPECIAL

- Resistant to most chemicals
- Good floor protection
- Non-marking
- Maintenance free
- Steel bearings may be substituted for nylon



Hard Rubber



Hard Rubber Grey

WHEEL				PART NUMBER				
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
2"	7/8"	100	31/32"	1/4"	-	Nylon	W-4002-HR	0.16
2 1/2"	1 1/8"	150	1 3/8"	5/16"	-	Nylon	W-4025-HR	0.32
3"	1 1/4"	250	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1930-HR	0.56
		250	1 3/8"	1/2"	5/16" * 3/8"	Steel	W-1930-HRG	0.56
		250	1 9/16"	3/8"	5/16"	Nylon	W-4003-HR	0.50
3 1/2"	1 1/4"	250	1 1/2"	3/8"	5/16"	Nylon	W-5235-HR	0.73
4"	1 1/4"	250	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1940-HR	0.90
		250	1 3/8"	1/2"	5/16" * 3/8"	Steel	W-1940-HRG	0.90
5"	1 1/4"	275	2"	3/8"	7/16"	Nylon	W-4004-HR	1.14
		250	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1950-HR	1.40
		250	1 1/2"	3/8"	-	Nylon	W-5005-HR	1.30