

FEATURES



ALGOOD

BEARINGS: Plain, Ball, Delrin, Nylon, Roller, Caged Roller
TEMPERATURE: -45°F to 180°F
COLOUR: Black
DESCRIPTION: This non-marking wheel features an exclusively developed thermoplastic nylon material which is excellent for high load capacities. The RollX™ wheel is extremely ergonomically efficient, as it requires minimum effort to roll & swivel with heavy loads. It resists hard impacts & is resistant to most chemicals, solvents, gases, acids, steam cleaning & does not absorb water! This wheel is ideal for industrial & institutional applications.
DUROMETER: 85 (+/-5) D Scale

EXCELLENT FOR

- Floor protection
- Factory use
- Waste bins
- Platform trucks
- Stock trucks
- Heavy material handling
- Easy rolling
- Heavy loads



ROLLX™



ROLLX™ (for WOW)



ROLLX™ HEAVY DUTY

OPTIONS

- BB Ball Bearing
- BR Bronze Bushing
- DB Delrin Bearing
- NB Nylon Roller Bearing
- NBSS Stainless Steel Nylon Roller Bearing
- RB Roller Bearing
- RBC Caged Roller Bearing
- RBSS Stainless Steel Roller Bearing
- SSW Steel Side Washer
- SWH Heat-treated Side Washer
- T Through Bore (2" wheel tread)
- TG Thread Guards

SPECIAL

- Resistant to most chemicals
- Non-marking
- Cart washable
- Maintenance free
- One piece solid RollX
- Same capacity as steel wheels
- Easy to assemble

WHEEL		PART NUMBER						
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
2 5/8"	1 1/2"	400	1 9/16"	12mm	-	Roller	W-54260-RX-RB-12MM	0.43
3"	1 1/2"	600	1 5/8"	3/8"	5/16"	Steel	W-6203-RX	0.48
		600	1 5/8"	1 3/16"	1/2" * 5/8"	Plain	W-6203-RX	0.42
		600	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6203-RX-RB	0.82
4"	1 3/8"	600	1 9/16"	1/2"	5/16" * 3/8"	Plain	W-5040-RX	0.66
		700	1 5/8"	3/8"	5/16"	Steel	W-6204-RX	0.77
	1 1/2"	700	1 5/8"	1 3/16"	1/2" * 5/8"	Plain	W-6204-RX	0.71
		700	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6204-RX-RB	1.11
5"	2"	800	2 3/16"	1 3/16"	-	Plain	W-7004-RX	0.63
		800	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7004-RX-RB	0.98
		800	1 5/8"	3/8"	5/16"	Steel	W-6205-RX	1.05
	1 1/2"	800	1 5/8"	1 3/16"	1/2" * 5/8"	Plain	W-6205-RX	0.97
		800	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6205-RX-RB	1.37
		1,000	2 3/16"	1 3/16"	-	Plain	W-7005-RX*	0.84
6"	2"	1,000	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7005-RX-RB	1.18
		1,800	2 3/16"	1 3/16"	-	Plain	W-7005-RXHD*	1.16
		1,800	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7005-RXHD-RB	1.50
	1 1/2"	1,200	2 3/16"	1 3/16"	-	Plain	W-7006-RX*	1.06
		1,200	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7006-RX-RB	1.40
		1,800	2 3/16"	1 3/16"	-	Plain	W-7006-RXHD*	1.57
8"	2"	1,800	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7006-RXHD-RB	1.98
		1,600	2 3/16"	1 3/16"	-	Plain	W-7006-RXW	1.64
		1,600	2 3/8"	1/2"	3/4"	Precision	W-7006-RXW-PB	2.11
		1,600	2 3/8"	1/2"	5/8" * 3/8"	Roller	W-7006-RXW-RB	2.04
8"	2"	1,400	2 3/16"	1 3/16"	-	Plain	W-7008-RX*	1.84
		1,400	2 3/8"	1/2"	5/8" * 3/4"	Roller	W-7008-RX-RB	2.10

* wheel has one closed side to eliminate side washer & for easier assembly