

Soft Rubber

80-350 LBS capacity

WHEELS

FEATURES

CONDUCTIVE AVAILABLE



ALGOOD

BEARINGS: Plain, Ball, Delrin, Nylon, Roller, Caged Roller, Steel
TEMPERATURE: -45°F to 160°F
COLOURS: Black, Grey (both are non-marking)
DESCRIPTION: Soft Rubber tread with a hard core for quiet movement, smooth ride and excellent floor protection. Used mainly for light loads.
DUROMETER: 75-85 A Scale

EXCELLENT FOR

- Economical
- Display racks
- Quiet, Cushion ride
- Good Floor Protection
- Hotel & Food Service equipment
- Shock & Vibration
- Restaurants & Hospitals
- Smooth Rolling
- Factory use
- Platform & Stock Trucks

OPTIONS

- BB Ball Bearing
- BR Bronze Bushing+
- DB Delrin Bearing
- NB Nylon Roller Bearing+
- NBSS Stainless Steel Nylon Roller Bearing+
- RB Roller Bearing+
- RBC Caged Roller Bearing+
- RBSS Stainless Steel Roller Bearing+
- SSW Steel Side Washer+
- SWH Heat-treated Side Washer+
- TG Thread Guards (on select wheels only)

+ available on 5"X2" wheels only

SPECIAL

- NB may be substituted for RB



SOFT RUBBER



SOFT RUBBER GREY



CONDUCTIVE SOFT RUBBER

WHEEL				PART NUMBER				
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
2"	7/8"	80	15/16"	1/4"	-	Steel	W-0800-CSR	0.12
		80	15/16"	1/4"	-	Steel	W-0800-SR	0.12
		80	15/16"	1/4"	-	Steel	W-0800-SRG	0.12
		80	31/32"	1/4"	-	Nylon	W-4002-SR	0.16
2 1/2"	7/8"	80	15/16"	1/4"	-	Steel	W-0820-CSR	0.20
		80	15/16"	1/4"	-	Steel	W-0820-SR	0.20
		80	15/16"	1/4"	-	Steel	W-0820-SRG	0.20
3"	1 1/8"	100	1 3/8"	5/16"	-	Nylon	W-4025-SR	0.31
		7/8"	100	15/16"	1/4"	-	Steel	W-0830-CSR
	100		15/16"	1/4"	3/8"	Steel	W-0830-SR	0.28
	100		15/16"	1/4"	3/8"	Steel	W-0830-SRG	0.28
	1 1/4"	150	1 3/16"	5/16"	-	Nylon	W-1030-SR	0.34
		250	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1930-SR	0.48
250		1 3/8"	1 1/8"	-	Plain	W-1930-SRG	0.50	
250		1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1930-SRG	0.48	
250	1 9/16"	5/16" A	3/8" A * 1/2" A	Nylon	W-1930-SRG	0.53		
250	1 5/8"	5/16"	3/8" * 1/2"	Ball	W-1930-SRG-BB	0.60		
200	1 9/16"	3/8"	5/16"	Nylon	W-4003-SR	0.50		
3 1/2"	1 1/4"	250	1 1/2"	3/8"	5/16"	Nylon	W-5235-SR	0.64

**CONDUCTIVE
SOFT RUBBER**

Algood certifies that upon leaving our factory, conductive wheels were tested for conductivity. The wheels were found to have an average electrical resistance from the hub to the tread of less than 250,000 ohms, and a maximum electrical resistance at any point from hub to tread of less than 1,000,000 ohms, which values are specified in Federal Specification FF-C-778, paragraphs 3.5 and 4.3.7 relating to electrical conductivity tests and standards for conductive caster wheels.

WHEEL					PART NUMBER				
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)	
4"	1"	150	1 3/16"	5/16"	3/8" * 1/2"	Nylon	W-1040-SR	0.74	
		150	1 3/16"	3/8"	5/16"	Steel	W-1040-SRG	0.74	
	1 1/4"	250	1 3/8"	1 1/8"	-	Plain	W-1940-SR	0.74	
		250	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1940-SR	0.76	
		250	1 9/16"	5/16" A	3/8" A * 1/2" A	Nylon	W-1940-SR	0.77	
		250	1 5/8"	5/16"	3/8" * 1/2"	Ball	W-1940-SR-BB	0.84	
		250	1 3/8"	1 1/8"	-	Plain	W-1940-SRG	0.74	
		250	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1940-SRG	0.76	
		250	1 9/16"	5/16" A	3/8" A * 1/2" A	Nylon	W-1940-SRG	0.77	
		250	1 5/8"	5/16"	3/8" * 1/2"	Ball	W-1940-SRG-BB	0.84	
	1 1/2"	250	2"	3/8"	7/16"	Nylon	W-4004-SR	1.14	
	5"	1"	150	1 3/16"	5/16"	3/8" * 1/2"	Nylon	W-1050-SR	0.90
			150	1 3/16"	1/2"	5/16" * 3/8"	Steel	W-1050-SRG	1.30
		1 1/4"	250	1 3/8"	1 1/8"	-	Plain	W-1950-SR	1.30
			250	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1950-SR	1.30
250			1 9/16"	5/16" A	3/8" A * 1/2" A	Nylon	W-1950-SR	1.34	
250			1 5/8"	5/16"	3/8" * 1/2"	Ball	W-1950-SR-BB	1.40	
250			1 3/8"	1 1/8"	-	Plain	W-1950-SRG	1.30	
250			1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1950-SRG	1.30	
250			1 9/16"	5/16" A	3/8" A * 1/2" A	Nylon	W-1950-SRG	1.34	
250			1 5/8"	5/16"	3/8" * 1/2"	Ball	W-1950-SRG-BB	1.40	
2"		350	2 3/16"	3/8"	-	Steel	W-5305-SR	2.04	
		350	2 3/16"	1 3/16"	-	Plain	W-7005-SR	1.83	
		350	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7005-SR-RB	2.26	