



ALTHANE™

WHEELS

750-1,400 LBS



FEATURES

BEARINGS: Plain, Nylon, Delrin, Steel Roller, Caged Roller
TEMPERATURE: -45°F to 180°F
COLOURS: Black
DUROMETER: 65-70 D scale

DESCRIPTION: The ALThane wheel is light in weight, very economical and high impact strength. Non-marking, non-chipping, oil and chemical resistant, non-absorbent and steam cleanable wheel provides for floor protection.

EXCELLENT FOR:

- Good Floor protection
- Factory use
- Waste bins
- Platform trucks
- Stock trucks
- Abusive applications
- Textile carts
- Hotel & Food service equipment



ALTHANE™



ALTHANE™(WOW)

OPTIONS:

- BB Ball Bearing
- DB Delrin Bearing
- NB Nylon Roller Bearing
- PB Precision Ball Bearing
- PBSS Stainless Steel Precision Bearing
- RB Roller Bearing
- RBC Caged Roller Bearing
- RBSS Stainless Steel Roller Bearing
- SSW Steel Side Washer
- SWH Heat-treated Side Washer
- T Through Bore (6"x2" ALTWOW wheel only)
- TG Thread Guards

WHEEL

PART NUMBER

Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
4"	2"	750	2 3/16"	1 3/16"	-	Plain Roller	W-7004-ALT	0.62
		750	2 3/8"	1/2"	3/8" * 5/8" * 3/4"		W-7004-ALT-RB	1.06
5"	2"	950	2 3/16"	1 3/16"	-	Plain Roller	W-7005-ALT	0.90
		950	2 3/8"	1/2"	3/8" * 5/8" * 3/4"		W-7005-ALT-RB	1.34
6"	2"	1,150	2 3/16"	1 3/16"	-	Plain Roller	W-7006-ALT	1.45
		1,150	2 3/8"	1/2"	3/8" * 5/8" * 3/4"		W-7006-ALT-RB	1.89
	2 1/2"	1,150	2 3/16"	1 3/16"	-	Plain Roller	W-7006-ALTWOW*	1.16
		1,150	2 3/8"	1/2"	3/8" * 5/8" * 3/4"		W-7006-ALTWOW-RB	1.60
8"	2"	1,200	2 3/16"	1 3/16"	-	Plain Roller	W-7008-ALT	2.00
		1,200	2 3/8"	1/2"	5/8" * 3/4"		W-7008-ALT-RB	2.44
	2 1/2"	1,300	2 3/4"	1 15/16"	-	Plain Roller	W-7106-ALT	1.60
		1,300	2 27/32"	3/4"	1" * 1 1/4"		W-7106-ALT-RB	3.25
2 1/2"	1,400	2 3/4"	1 15/16"	-	Plain Roller	W-7108-ALT	2.90	
	1,400	2 27/32"	3/4"	1" * 1 1/4"		W-7108-ALT-RB	4.55	

SPECIAL:

- Resistant to most chemicals
- Non-marking
- Moisture friendly
- Maintenance free
- One piece solid ALThane

* Custom sizes available

- ◆ wheel has one closed side to eliminate side washer and for easier assembly