

CENTAUR WHEEL® CAPACITIES UP TO 550 LBS



Centaur Wheel

OPERATING TEMPERATURE: -22F to 176F Continuous
-40F to 212 Intermittently

HARDNESS: 75-80 Shore A

ABRASION: 250-300 mm³

DENSITY: 1.14

ATTRIBUTES

OPERATING CHARACTERISTICS:

- Puncture proof,
- Quiet rolling,
- Cushioned,
- Resilient,
- Excellent life expectancy,
- Low starting effort under load on uneven floors.

EXCELLENT FOR:

- Dollies
- Floor Protection
- Quiet Operation
- Stock Trucks
- Wheelers
- Hand Dollies

The Centaur Wheel features a thick solid rubber tire mounted to bolted-steel center rims. The rubber is compression-molded from a blend of granulated (crumb) rubber recycled from used car and truck tires. Heavy-duty ball bearings are encased within the rim set and provide excellent roll-ability. This wheel is commonly used in hangers and factories throughout North America.

Good abrasion resistance and excellent resistance to water (68F) and saturated steam, make this a tough and rugged wheel that is often imitated but never duplicated.

| Diameter (Ins.) | Tread Width | Bearing Type | Bore Size | Capacity (LBS) | Hub Length | Wheel Weight (lbs) | Part Number |
|-----------------|-------------|--------------|-----------|----------------|-------------------|--------------------|------------------|
| 6" | 1.25" | BALL | 3/4" | 350 | 2 1/4" - Centered | 2.35 | W-7006-CT-BB-3/4 |
| 8" | 1.5" | BALL | 3/4" | 400 | 2 1/4" - Centered | 3.51 | W-7008-CT-BB-3/4 |
| 10" | 1.5" | BALL | 3/4" | 500 | 2 1/4" - Centered | 4.76 | W-7010-CT-BB-3/4 |
| 12" | 1.5" | BALL | 3/4" | 550 | 2 1/4" - Centered | 6.88 | W-7012-CT-BB-3/4 |