

Foam Pneumatic

210-250 LBS capacity

WHEELS

FEATURES



ALGOOD

BALL BEARINGS: Ball
TEMPERATURE: -20°F to 130°F
FINISH: Plastic Grey Hub
DESCRIPTION: Foam Pneumatic wheels are excellent for applications where floor and equipment protection is vital. The foam fill provides for shock absorption, quiet operation and ease of rolling. Excellent for delicate materials and uneven and rough floor surfaces. For manual operation only.

EXCELLENT FOR

- Uneven floors such as agricultural, institutional & industrial
- Shock absorbing uses for indoor & outdoor rough terrain



PNEUMATIC FOAM



PNEUMATIC FOAM GREY

HUB SIZE

| HUB LENGTH | CODE# |
|------------|-------|
| 2" | A |
| 2 1/4" | B |
| 2 1/2" | C |
| 2 5/8" | D |
| 3" | E |
| 3 1/4" | I |
| 4" | F |
| 4 1/4" | H |

WHEEL

PART NUMBER

| Diameter | Tread Width | Capacity Lbs. | Hub Length | Hub Type | Tire Colour | Standard Bore | Alternative Bore | Bearing Type | Part Number | Wheel Weight (lbs) |
|----------|-------------|---------------|------------|----------|-------------|---------------|------------------|--------------|-----------------|--------------------|
| 6" | 2" | 210 | 2 1/2" | Center | Black | 1/2" | 5/8" * 3/4" | Ball | W-7006-PFCC-BB | 0.79 |
| | | 210 | 2 1/2" | Center | Grey | 1/2" | 5/8" * 3/4" | Ball | W-7006-PFCCG-BB | 0.79 |
| 8" | 2 1/2" | 235 | 3" | Center | Black | 1/2" | 5/8" * 3/4" | Ball | W-7908-PFCE-BB | 1.70 |
| | | 235 | 3" | Center | Grey | 1/2" | 5/8" * 3/4" | Ball | W-7908-PFCEG-BB | 1.70 |
| 10" | 3" | 250 | 2 1/4" | Offset | Black | 5/8" | -- | Ball | W-7910-PFOB | 2.10 |
| | | 250 | 2 1/4" | Offset | Black | 5/8" | 1/2" * 3/4" | Ball | W-7910-PFOB-BB | 2.51 |
| | | 250 | 4" | Center | Black | 1/2" | 5/8" * 3/4" | Ball | W-7910-PFCF-BB | 2.52 |
| | | 250 | 4" | Center | Grey | 1/2" | 5/8" * 3/4" | Ball | W-7910-PFCFG-BB | 2.52 |