



HARD RUBBER

WHEELS

125-325 LBS



FEATURES

BEARINGS: Nylon, Steel
TEMPERATURE: -45°F to 160°F
COLOURS: Black, Grey
DUROMETER: 70-80 D scale

DESCRIPTION: This Solid Hard Rubber wheel is used for higher load capacities than soft rubber. Good floor protection and easier mobility. Will not develop flat spots under standing loads. High resistance to oil, grease and mild or diluted acids.

EXCELLENT FOR:

- Economical
- Resistant to most chemicals
- Rejects floor debris
- Small waste bins
- Factory use
- Textile carts
- Abusive applications



HARD RUBBER



HARD RUBBER GREY

WHEEL

PART NUMBER

Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
2"	7/8"	125	3 1/32"	1/4"	-	Nylon	W-4002-HR	0.16
3"	1 1/4"	275	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1930-HR	0.56
		275	1 3/8"	1/2"	5/16" * 3/8"	Steel	W-1930-HRG	0.56
		275	1 9/16"	3/8"	5/16"	Nylon	W-4003-HR	0.50
4"	1 1/4"	300	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1940-HR	0.90
		300	1 3/8"	1/2"	5/16" * 3/8"	Steel	W-1940-HRG	0.90
5"	1 1/4"	325	1 3/8"	5/16"	3/8" * 1/2"	Steel	W-1950-HR	1.40

OPTIONS:

TG Thread Guards
 (1900 series wheels only)

SPECIAL:

Resistant to most chemicals
 Good floor protection
 Non-marking
 Maintenance free
 Steel bearings may be substituted for nylon