



MOLDON URETHANE WHEELS

600-6,600 LBS

FEATURES

BEARINGS: Plain, Ball, Delrin, Nylon, Roller, Caged Roller, Tapered
TEMPERATURE: -20°F to 175°F
COLOURS: Black Core, Red Tread and Black Core, Orange Rust Tread
DUROMETER: 92 - 95 A Scale for UR, 70 D Scale for URH

DESCRIPTION: Moldon Urethane tread is secured to semi steel core. This wheel allows for an easy, smooth, quiet ride. The Moldon Urethane provides excellent floor protection while carrying extremely heavy loads. Tread is resistant to most chemicals.



EXCELLENT FOR:

- Floor protection
- Factory use
- Abusive applications
- Platform and Stock trucks
- Resistant to most chemicals
- Heavy material handling
- Outdoor use
- Heavy loads
- Smooth Rolling
- Longevity



MOLDON URETHANE



MOLDON URETHANE
CROWN



MOLDON URETHANE
HEAVY DUTY

OPTIONS:

- BB Ball Bearing
 BR Bronze Bushing
 DB Delrin Bearing
 NB Nylon Roller Bearing
 NBSS Stainless Steel Nylon Roller Bearing
 RB Roller Bearing
 RBC Caged Roller Bearing
 RBSS Stainless Steel Roller Bearing
 SSW Steel Side Washer
 SWH Heat-treated Side Washer
 TB Tapered Bearing
 TG Thread Guards

WHEEL							PART NUMBER		
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)	
4"	1 1/2"	600	1 5/8"	1 3/16"	—	Plain	W-6204-UR	1.66	
		600	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6204-UR-RB	1.96	
	2"	800	2 3/16"	1 3/16"	—	Plain	W-7004-UR	2.30	
		800	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7004-UR-RB	2.74	
		800	2 3/16"	3/16"	—	Plain	W-7004-URC	2.42	
		800	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7004-URC-RB	2.86	
	5"	1 1/2"	800	1 5/8"	1 3/16"	—	Plain	W-6205-UR	2.68
			800	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6205-UR-RB	2.98
2"		1,200	2 3/16"	1 3/16"	—	Plain	W-7005-UR	3.34	
		1,200	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7005-UR-RB	3.78	
	1,200	2 3/16"	1 3/16"	—	Plain	W-7005-URC	2.64		
	1,200	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7005-URC-RB	3.08		
6"	1 1/2"	800	1 5/8"	1 3/16"	—	Plain	W-6206-UR	3.16	
		800	1 13/16"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-6206-UR-RB	3.46	
	2"	1,250	2 3/16"	1 3/16"	—	Plain	W-7006-UR	4.16	
		1,250	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7006-UR-RB	4.60	
		1,250	2 3/16"	1 3/16"	—	Plain	W-7006-URC	3.57	
		1,250	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7006-URC-RB	4.01	
	2 1/2"	1,600	2 3/4"	1 15/16"	—	Plain	W-7106-UR	6.32	
		1,600	2 27/32"	3/4"	1" * 1 1/4"	Roller	W-7106-UR-RB	7.97	
	3"	2,000	3 1/4"	1 15/16"	—	Plain	W-7506-UR	7.90	
		2,000	3 7/16"	3/4"	1" * 1 1/4"	Roller	W-7506-UR-RB	9.79	
		2,000	3 1/4"	3/4"	1" * 1 1/4"	Tapered	W-9106-UR-TB *	11.22	
		3,000	3 1/2"	1 1/4"	3/4" * 1"	Tapered	W-9106-URH-TB*	9.50	

* 1" Thick tread

WHEELS

WHEEL						PART NUMBER		
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
6"	4"	3,000	4 1/4"	2 7/16"	-	Plain	W-9664-URR*	17.00
		3,000	4 1/4"	1 1/4"	1 1/2"	Roller	W-9664-URR-RB*	17.00
		3,000	4 1/2"	1 1/4"	1"	Tapered	W-9664-URR-TB*	17.00
		3,600	4 1/4"	2 7/16"	-	Plain	W-9664-URH*	17.00
		3,600	4 1/4"	1 1/4"	1" * 1 1/2"	Roller	W-9664-URH-RB*	17.00
		3,600	4 1/2"	1 1/4"	1"	Tapered	W-9664-URH-TB*	17.00
		3,600	4 1/2"	1 1/4"	1"	Tapered	W-9664-URH-TB*	17.00
8"	2"	1,500	2 3/16"	1 3/16"	-	Plain	W-7008-UR	6.20
		1,500	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7008-UR-RB	6.64
		1,500	2 3/16"	1 3/16"	-	Plain	W-7008-URC	5.76
		1,500	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7008-URC-RB	6.20
	2 1/2"	2,000	2 3/4"	1 15/16"	-	Plain	W-7108-UR	11.22
		2,000	2 27/32"	3/4"	1" * 1 1/4"	Roller	W-7108-UR-RB	12.87
	3"	2,500	3 1/4"	1 15/16"	-	Plain	W-7508-UR	12.34
		2,500	3 7/16"	3/4"	1" * 1 1/4"	Roller	W-7508-UR-RB	14.23
		2,500	3 1/4"	3/4"	1" * 1 1/4"	Tapered	W-9108-UR-TB*	17.70
		3,700	3 1/2"	1 1/4"	3/4" * 1"	Tapered	W-9108-URH-TB *	17.00
	4"	3,800	4 1/4"	2 7/16"	-	Plain	W-9684-URR	20.00
		3,800	4 1/4"	1 1/4"	1 1/2"	Roller	W-9684-URR-RB	20.00
		3,800	4 1/2"	1 1/4"	1"	Tapered	W-9684-URR-TB	20.00
		4,500	4 1/4"	2 7/16"	-	Plain	W-9684-URH	20.00
		4,500	4 1/4"	1 1/4"	1" * 1 1/2"	Roller	W-9684-URH-RB	20.00
		4,500	4 1/2"	1 1/4"	1"	Tapered	W-9684-URH-TB	20.00
10"	2 1/2"	2,200	2 3/4"	1 15/16"	-	Plain	W-7110-UR	14.02
		2,200	2 27/32"	3/4"	1" * 1 1/4"	Roller	W-7110-UR-RB	15.67
	3"	3,000	3 1/4"	1 15/16"	-	Plain	W-7510-UR	16.64
		3,000	3 7/16"	3/4"	1" * 1 1/4"	Roller	W-7510-UR-RB	18.53
		3,000	3 1/4"	3/4"	1" * 1 1/4"	Tapered	W-9110-UR-TB*	23.46
		4,400	3 1/2"	1 1/4"	3/4" * 1"	Tapered	W-9110-URH-TB*	24.00

* 1" Thick tread

WHEELS

WHEEL							PART NUMBER	
Diameter 	Tread Width 	Capacity Lbs. 	Hub Length 	Standard Bore 	Alternative Bore 	Bearing Type 	Part Number 	Wheel Weight (lbs) 
10"	4"	5,000	4 1/4"	2 7/16"	-	Plain	W-96104-URR*	33.00
		5,000	4 1/4"	1 1/4"	1"* 1 1/2"	Roller	W-96104-URR-RB*	33.00
		5,000	4 1/2"	1 1/4"	1"	Tapered	W-96104-URR-TB*	33.00
		6,000	4 1/4"	2 7/16"	-	Plain	W-96104-URH*	33.00
		6,000	4 1/4"	1 1/4"	1"* 1 1/2"	Roller	W-96104-URH-RB*	33.00
		6,000	4 1/2"	1 1/4"	1"	Tapered	W-96104-URH-TB*	33.00
		12"	2 1/2"	2,500	2 3/4"	1 15/16"	-	Plain
2,500	2 27/32"			3/4"	1"* 1 1/4"	Roller	W-7112-UR-RB	20.81
3"	3,500		3 1/4"	1 15/16"	-	Plain	W-7512-UR	21.74
	3,500		3 7/16"	3/4"	1"* 1 1/4"	Roller	W-7512-UR-RB	23.63
	3,500		3 1/4"	3/4"	-	Tapered	W-9112-UR-TB *	31.22
	4,600		3 1/2"	1 1/4"	3/4"* 1"	Tapered	W-9112-URH-TB *	24.00
4"	5,500		4 1/4"	2 7/16"	-	Plain	W-96124-URR *	30.00
	5,500		4 1/4"	1 1/4"	1 1/2"	Roller	W-96124-URR-RB *	30.00
	5,500		4 1/2"	1 1/4"	1"	Tapered	W-96124-URR-TB *	30.00
	6,600		4 1/4"	2 7/16"	-	Plain	W-96124-URH *	30.00
	6,600		4 1/4"	1 1/4"	1"* 1 1/2"	Roller	W-96124-URH-RB *	30.00
	6,600		4 1/2"	1 1/4"	1"	Tapered	W-96124-URH-TB *	30.00

* 1" Thick tread