

# SHOPPING CART

WHEELS

30-300 LBS



## FEATURES

**BEARINGS:** Plain, Ball, Precision  
**TEMPERATURE:** -45°F to 180°F  
**COLOURS:** Grey Core, Navy Tread (1 1/4" tread);  
 White Core, Black Tread (all other tread widths)  
**DUROMETER:** 90 - 95 A Scale

**DESCRIPTION:** This non-marking Urethane treaded wheel is securely bonded mechanically to its Polyolefin core to prevent separation. It is highly resistant to chemicals and is excellent for all floor surfaces. This wheel provides for high load capacities and is rust proof. 100% Moisture Friendly.

### EXCELLENT FOR:

- Shopping Carts
- Food equipment
- Mobile stock shelves
- Airports
- Bakery equipment
- Floor protection



MOLDON POLYOLEFIN URETHANE



MOLDON POLYOLEFIN URETHANE  
 (♦ OLD STYLE BB-TG)

### OPTIONS:

- BB Ball Bearing  
 (3 1/2" PLY wheel only)  
 PB Precision Ball Bearing  
 (3", 4", & 5" PLY wheels only)  
 PBSS Stainless Steel Precision Ball Bearing  
 (3", 4", & 5" PLY wheels only)  
 TG Thread Guards  
 (1 1/4" tread only)

### SPECIAL:

- Non-marking
- Moisture friendly
- High quality ball bearing
- Long life tread
- Resistant to most chemicals
- Custom colours available upon request

WHEEL							PART NUMBER		
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)	
1 1/4"	9/16"	30	5/8"	3/16"	-	Plain	W-4125-PLY	0.03	
2"	15/16"	90	1"	1/4"	-	Plain	W-4002-PLY	0.09	
2 1/2"	1 1/8"	160	1 13/32"	5/16"	-	Plain	W-4025-PLY	0.32	
3 1/2"	1 1/4"	250	1 9/16"	3/8"	5/16"	Ball	W-5235-PLY-BB-TG	0.53	
3"	1 1/4"	300	1 5/8"	3/8"	5/16"	Precision	W-1930-PLY-PB-TG	0.34	
4"	1 1/4"	300	1 5/8"	3/8"	5/16"	Precision	W-1940-PLY-PB-TG	0.60	
5"	1 1/4"	300	1 5/8"	3/8"	5/16"	Precision	W-1950-PLY-PB-TG	0.80	

♦ Old Style Moldon Polyolefin Custom order run 2,500 pieces minimum. Call for availability

\* Stainless Steel Precision Ball Bearing (PBSS) Special Order. Call for availability