




STEEL DUCTILE FORGED

WHEELS 125-20,000 LBS




FEATURES

BEARINGS: Plain, Ball, Delrin, Nylon, Roller, Caged Roller, Tapered
TEMPERATURE: -45°F to 180°F (standard),
 -45°F to 800°F with Roller bearing & Steel side washers
COLOURS: Steel Grey

DESCRIPTION: Cast Iron, Ductile Iron, Forged Steel wheels are toughened for strength and longevity. While the steel wheel is always competitive for its weight, it is mainly used for rugged and concrete floors. This wheel could cause floor wear and it is rather noisy. However, Solid Steel Crowned (SSC) wheels are available for less damage.

EXCELLENT FOR:

- Floor protection
- Factory use
- Waste bins
- Platform trucks
- Stock trucks
- Heavy material handling
- Easy rolling
- Heavy loads




SOLID STEEL (SS)



SOLID STEEL HEAVY DUTY



SEMI STEEL (ST)



FORGED STEEL



DUCTILE IRON

WHEEL

PART NUMBER

Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
2"	15/16"	125	1"	1/4"	—	Plain	W-4002-ST	.50
2 1/2"	1"	250	1 3/8"	5/16"	—	Plain	W-4025-ST	.75
3"	1 1/4"	300	1 1/2"	1/2"	5/16 "x 3/8"	Plain	W-1930-SS	1.04
4"	1 1/4"	300	1 1/2"	1/2"	5/16 "x 3/8"	Plain	W-1940-SS	1.97
	1 1/2"	600	1 5/8"	1 3/16"	—	Plain	W-6204-SS	2.36
		600	1 13/16"	1/2"	5/16 "x 3/8 "x 5/8 "x 3/4"	Roller	W-6204-SS-RB	2.66
	2"	700	2 3/16"	1 3/16"	—	Plain	W-7004-SS	2.60
5"	1 1/4"	700	2 3/8"	1/2"	3/8 "x 5/8 "x 3/4"	Roller	W-7004-SS-RB	3.04
		700	2 3/8"	1/2"	3/8 "x 5/8 "x 3/4"	Roller	W-7004-SS-RB	3.04
	1 1/4"	350	1 1/2"	1/2"	5/16 "x 3/8"	Plain	W-1950-SS	2.19
	1 1/2"	600	1 5/8"	1 3/16"	—	Plain	W-6205-SS	2.98
		600	1 13/16"	1/2"	5/16 "x 3/8 "x 5/8 "x 3/4"	Roller	W-6205-SS-RB	3.28
	2"	1,000	2 3/16"	1 3/16"	—	Plain	W-7005-SS	3.54
		1,000	2 3/8"	1/2"	3/8 "x 5/8 "x 3/4"	Roller	W-7005-SS-RB	3.98
		1,750	2 3/16"	1 3/16"	—	Plain	W-7005-DIC	4.12
		1,750	2 3/8"	1/2"	3/8 "x 5/8 "x 3/4"	Roller	W-7005-DIC-RB	4.56
6"	1 1/2"	700	1 5/8"	1 3/16"	—	Plain	W-6206-SS	4.18
		700	1 13/16"	1/2"	5/16 "x 3/8 "x 5/8 "x 3/4"	Roller	W-6206-SS-RB	4.48
	2"	1,200	2 3/16"	1 3/16"	—	Plain	W-7006-SS	4.68
		1,200	2 3/8"	1/2"	3/8 "x 5/8 "x 3/4"	Roller	W-7006-SS-RB	5.12
		1,750	2 3/16"	1 3/16"	—	Plain	W-7006-DIC	5.14
		1,750	2 3/8"	1/2"	3/8 "x 5/8 "x 3/4"	Roller	W-7006-DIC-RB	5.58
	2 1/2"	1,800	2 3/4"	1 15/16"	—	Plain	W-7106-SS	9.52
		1,800	2 27/32"	3/4"	1 "x 1 1/4"	Roller	W-7106-SS-RB	11.17

OPTIONS:

- BB Ball Bearing
- BR Bronze Bushing
- DB Delrin Bearing
- NB Nylon Roller Bearing
- NBSS Stainless Steel Nylon Roller Bearing
- RB Roller Bearing
- RBC Caged Roller Bearing
- RBSS Stainless Steel Roller Bearing
- SSW Steel Side Washer
- SWH Heat-treated Side Washer
- TB Tapered Bearing
- TG Thread Guards

STEEL DUCTILE FORGED

WHEELS

WHEELS

WHEEL						PART NUMBER		
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
6"	3"	2,500	3 1/4"	1 15/16"	-	Plain	W-7506-SS	11.70
		2,500	3 7/16"	3/4"	1" * 1 1/4"	Roller	W-7506-SS-RB	13.90
		2,500	3 1/4"	1 15/16"	1 13/16"	Plain	W-9106-SSR	12.00
		2,500	3 1/4"	3/4"	1" * 1 1/4"	Roller	W-9106-SSR-RB	12.00
		2,500	3 1/2"	3/4"	1"	Tapered	W-9106-SSR-TB	12.00
		3,500	3 7/16"	3/4"	-	Tapered	W-9106-SS-TB	10.10
		4,500	3 7/16"	3/4"	-	Tapered	W-9106-DI-TB	11.25
		6,000	3 1/4"	2 7/16"	-	Plain	W-9106-FSR	20.00
		6,000	3 1/4"	3/4"	1" * 1 1/4" * 1 1/2"	Roller	W-9106-FSR-RB	20.00
		10,000	3 1/2"	1 1/4"	1"	Tapered	W-9106-FSR-TB	20.00
		17,000	3 1/4"	3 1/8"	-	Plain	W-9106-FSH	22.00
		17,000	3 1/2"	1 1/4"	1 1/2"	Tapered	W-9106-FSH-TB	22.00
8"	2"	1,400	2 3/16"	1 3/16"	-	Plain	W-7008-SS	7.04
		1,400	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7008-SS-RB	7.48
		1,400	2 3/16"	1 3/16"	-	Plain	W-7008-SSC	6.85
		1,400	2 3/8"	1/2"	3/8" * 5/8" * 3/4"	Roller	W-7008-SSC-RB	7.29
	2 1/2"	1,800	2 3/4"	1 15/16"	-	Plain	W-7108-SS	14.86
		1,800	2 27/32"	3/4"	1" * 1 1/4"	Roller	W-7108-SS-RB	16.51
	3"	2,500	3 1/4"	1 15/16"	-	Plain	W-7508-SS	18.00
		2,500	3 7/16"	3/4"	1" * 1 1/4"	Roller	W-7508-SS-RB	20.20
		3,500	3 7/16"	3/4"	-	Tapered	W-9108-SS-TB	13.02
		3,500	3 1/4"	1 15/16"	-	Plain	W-9108-SSR	15.00
		3,500	3 1/4"	3/4"	1" * 1 1/4"	Roller	W-9108-SSR-RB	15.00
		4,500	3 1/2"	3/4"	1" * 1 1/4"	Tapered	W-9108-SSR-TB	25.00
		4,000	3 1/4"	1 15/16"	1 13/16"	Plain	W-9108-STR	18.00
		4,000	3 1/4"	3/4"	1" * 1 1/4"	Roller	W-9108-STR-RB	20.00
		4,000	3 1/2"	3/4"	1 1/4"	Tapered	W-9108-STR-TB	20.00
		4,750	3 7/16"	3/4"	-	Tapered	W-9108-DI-TB	16.32
		4,500	3 1/4"	1 15/16"	-	Plain	W-9108-FSR	18.50
		4,500	3 1/4"	3/4"	1" * 1 1/4"	Roller	W-9108-FSR-RB	18.50
		5,500	3 1/2"	3/4"	1"	Tapered	W-9108-FSR-TB	18.50
	4"	5,000	4 1/4"	2 7/16"	-	Plain	W-9684-SSR	28.00
		5,000	4 1/4"	1 1/4"	1"	Roller	W-9684-SSR-RB	28.00
		5,000	4 1/2"	1 1/4"	1"	Tapered	W-9684-SSR-TB	28.00
		8,400	4 1/4"	2 7/16"	-	Plain	W-9684-FSR	37.00
		8,400	4 1/4"	1 1/4"	1" * 1 1/2"	Roller	W-9684-FSR-RB	37.00
		10,000	4 1/2"	1 1/4"	1"	Tapered	W-9684-FSR-TB	37.00
		20,000	4 1/4"	3 1/8"	-	Plain	W-9684-FSH	37.00
		20,000	4 1/2"	1 1/4"	1 1/2"	Tapered	W-9684-FSH-TB	37.00
10"	2 1/2"	2,000	2 3/4"	1 15/16"	-	Plain	W-7110-SS	15.54
		2,000	2 27/32"	3/4"	1" * 1 1/4"	Roller	W-7110-SS-RB	17.22
		3,300	2 3/4"	1 15/16"	-	Plain	W-7110-SSR	15.50
		3,300	2 27/32"	3/4"	1" * 1 1/4"	Roller	W-7110-SSR-RB	17.25

STEEL DUCTILE FORGED

WHEELS

WHEELS

WHEEL							PART NUMBER	
Diameter	Tread Width	Capacity Lbs.	Hub Length	Standard Bore	Alternative Bore	Bearing Type	Part Number	Wheel Weight (lbs)
10"	3"	2,500	3 1/4"	1 15/16"	-	Plain	W-7510-SS	18.72
		2,500	3 7/16"	3/4"	1" 1 1/4"	Roller	W-7510-SS-RB	20.61
		3,500	3 7/16"	3/4"	-	Tapered	W-9110-SS-TB	18.46
		3,500	3 1/4"	1 15/16"	2 7/16"	Plain	W-9110-SSR	30.00
		3,500	3 1/4"	3/4"	1" 1 1/4" 1 1/2"	Roller	W-9110-SSR-RB	30.00
		3,500	3 1/2"	3/4"	1" 1 1/4"	Tapered	W-9110-SSR-TB	30.00
		4,000	3 1/4"	1 15/16"	1 13/16"	Plain	W-9110-STR	23.00
		4,000	3 1/4"	3/4"	1" 1 1/4"	Roller	W-9110-STR-RB	25.00
		4,000	3 1/2"	3/4"	1 1/4"	Tapered	W-9110-STR-TB	25.00
		5,000	3 7/16"	3/4"	-	Tapered	W-9110-DI-TB	27.56
		5,000	3 1/4"	1 15/16"	-	Plain	W-9110-FSR	28.00
		5,000	3 1/4"	3/4"	1" 1 1/4"	Roller	W-9110-FSR-RB	28.00
		6,000	3 1/2"	3/4"	1" 1 1/4"	Tapered	W-9110-FSR-TB	28.00
		6,500	3 1/4"	2 7/16"	-	Plain	W-9110-FSH	28.00
		6,000	3 1/4"	1"	3/4" 1" 1/4" 1 1/2"	Roller	W-9110-FSH-RB	28.00
		6,500	3 1/2"	1 1/4"	1" 1 1/2"	Tapered	W-9110-FSH-TB	28.00
	4"	6,000	4 1/4"	2 7/16"	-	Plain	W-96104-SSR	32.00
		6,000	4 1/4"	1 1/4"	1"	Roller	W-96104-SSR-RB	32.00
		6,000	4 1/2"	1 1/4"	1"	Tapered	W-96104-SSR-TB	32.00
		8,400	4 1/4"	2 7/16"	-	Plain	W-96104-FSR	48.00
		8,400	4 1/4"	1 1/4"	1" 1 1/2"	Roller	W-96104-FSR-RB	48.00
		10,000	4 1/2"	1 1/4"	1"	Tapered	W-96104-FSR-TB	48.00
		20,000	4 1/4"	3 1/8"	-	Plain	W-96104-FSH	48.00
		20,000	4 1/2"	1 1/4"	1 1/2"	Tapered	W-96104-FSH-TB	48.00
12"	2 1/2"	2,000	2 3/4"	1 15/16"	-	Plain	W-7112-SS	18.78
		2,000	2 27/32"	3/4"	1" 1 1/4"	Roller	W-7112-SS-RB	20.43
	3"	2,500	3 1/4"	1 15/16"	-	Plain	W-7512-SS	24.00
		2,500	3 7/16"	3/4"	1" 1 1/4"	Roller	W-7512-SS-RB	25.89
		3,500	3 7/16"	3/4"	-	Tapered	W-9112-SS-TB	28.66
		2,500	3 1/4"	1 15/16"	-	Plain	W-9112-SSR	26.00
		2,500	3 1/4"	3/4"	1" 1 1/4"	Roller	W-9112-SSR-RB	26.00
		2,500	3 1/4"	3/4"	1" 1 1/4"	Tapered	W-9112-SSR-TB	26.00
		5,500	3 7/16"	3/4"	-	Tapered	W-9112-DI-TB	30.87
	4"	7,500	4 1/4"	2 7/16"	-	Plain	W-96124-DIR	53.00
		7,500	4 1/4"	1 1/4"	1" 1 1/2"	Roller	W-96124-DIR-RB	53.00
		7,500	4 1/2"	1 1/4"	1"	Tapered	W-96124-DIR-TB	53.00
		7,500	4 1/4"	1 1/4"	1 1/2"	Roller	W-96124-FSR-RB	130.00
		20,000	4 1/4"	2 7/16"	-	Plain	W-96124-FSH	130.00
		20,000	4 1/2"	1 1/4"	-	Tapered	W-96124-FSH-TB	130.00
16"	4"	7,500	4 1/4"	2 7/16"	-	Plain	W-96164-SSR	72.00
		7,500	4 1/4"	1 1/4"	1" 1 1/2"	Roller	W-96164-SSR-RB	72.00
		7,500	4 1/2"	1 1/4"	1" 1 1/2"	Tapered	W-96164-SSR-TB	72.00