

EZ WHEEL®**CAPACITIES UP TO 675 LBS**

EZ

DESCRIPTION: Thermoplastic Elastomer Tread bonded to Polyolefin Hubs**OPERATING TEMPERATURE:** Minus 40F to 180F**HARDNESS:** 65+/-5 Shore A

The EZ (Flat) and EZC (Crowned) Wheels feature Thermoplastic Elastomer bonded to a Polyolefin hub. Quickly becoming a staple product in both institutional and industrial environments because of its resiliency (65 +/-5 Durometer Shore A) and impact resistance, the EZ/EZC provides both an economical and tough design providing years of trouble free performance.

The EZ/EZC is available with a number of bearings options to suit your application. Please consult Caster World for the best suited option.



EZC

OPTIONS**OPERATING CHARACTERISTICS:**

- Puncture proof,
- Quiet rolling,
- Cushioned,
- Resilient,
- Excellent life expectancy,
- Low starting effort under load on uneven floors.

BEARING OPTIONS:

- "BB" – Ball Bearings
- "BBSS" – Stainless Steel Ball Bearings
- "RB" – Roller Bearing
- "RBC" – Caged Roller Bearing
- "DB" – Delrin Bearing

EXCELLENT FOR:

- Quiet Operation
- Floor Protection
- Institutional Applications
- Moist Environments
- Hotel & Food Service Equipment
- Ergonomic Applications
- Shock and Vibration
- Waste Bins
- Factory Applications
- Textile Carts

EZ WHEEL®

CAPACITIES UP TO 675 LBS

Diameter (Ins.)	Tread Width	Bearing Type	Tread Profile	Capacity (LBS)	Bore Size	Hub Length	Wheel Weight (lbs)	Part Number
3"	1 1/4"	BALL	Flat	200	3/8"	1 5/8"	0.5	W-5203-EZ-PB-3/8
3"	1 1/4"	Delrin	Flat	200	1/2"	1 5/8"	0.5	W-5203-EZ-DB-1/2
3"	1 1/4"	BALL	Crown	175	3/8"	1 5/8"	0.25	W-5203-EZC-PB-3/8
3"	1 1/4"	Delrin	Crown	175	1/2"	1 5/8"	0.25	W-5203-EZC-DB-1/2
3 1/2"	1 1/4"	BALL	Flat	250	3/8"	1 5/8"	0.5	W-5235-EZ-PB-3/8
3 1/2"	1 1/4"	Delrin	Flat	250	1/2"	1 5/8"	0.5	W-5235-EZ-DB-1/2
3 1/2"	1 1/4"	BALL	Crown	225	3/8"	1 5/8"	0.5	W-5235-EZC-PB-3/8
3 1/2"	1 1/4"	Delrin	Crown	225	1/2"	1 5/8"	0.5	W-5235-EZC-DB-1/2
4"	1 1/4"	BALL	Flat	275	3/8"	1 5/8"	0.75	W-5204-EZ-PB-3/8
4"	1 1/4"	Delrin	Flat	275	1/2"	1 5/8"	0.75	W-5204-EZ-DB-1/2
4"	1 1/4"	BALL	Crown	250	3/8"	1 5/8"	0.5	W-5204-EZC-PB-3/8
4"	1 1/4"	Delrin	Crown	250	1/2"	1 5/8"	0.5	W-5204-EZC-DB-1/2
4"	2"	No Bearing	Flat	350	1 3/16"	2 3/16"	0.65	W-6704-EZ-1 3/16
4"	2"	No Bearing	Crown	275	1 3/16"	2 3/16"	0.6	W-6704-EZC-1 3/16
4"	2"	Roller	Flat	350	3/4"	2 3/16"	0.98	W-6704-EZ-RB-3/4
4"	2"	Roller	Crown	275	3/4"	2 3/16"	0.92	W-6704-EZC-RB-3/4
4"	2"	BALL	Flat	350	1/2"	2 7/16"	0.98	W-6704-EZ-BB-1/2
4"	2"	BALL	Crown	275	1/2"	2 7/16"	0.92	W-6704-EZC-BB-1/2
4"	2"	Annular Ball	Flat	350	1/2"	2 7/16"	0.98	W-6704-EZ-PBC-1/2
4"	2"	Annular Ball	Crown	275	1/2"	2 7/16"	0.92	W-6704-EZC-PBC-1/2
4"	2"	Flanged Delrin	Flat	350	1/2", 3/4"	2 3/8"	0.73	W-6704-EZ-DB-**
4"	2"	Flanged Delrin	Crown	275	1/2", 3/4"	2 3/8"	0.68	W-6704-EZC-DB-**
4"	2"	Delrin Bushing	Flat	350	1/2", 3/4"	2 3/16"	0.73	W-6704-EZ-DBC-**
4"	2"	Delrin Bushing	Crown	275	1/2", 3/4"	2 3/16"	0.68	W-6704-EZC-DBC-**

** - Include Bearing Size

EZ WHEEL®

CAPACITIES UP TO **675 LBS**

Diameter (Ins.)	Tread Width	Bearing Type	Tread Profile	Capacity (LBS)	Bore Size	Hub Length	Wheel Weight (lbs)	Part Number
5"	1 1/4"	BALL	Flat	300	3/8"	1 5/8"	0.75	W-5205-EZ-PB-3/8
5"	1 1/4"	Delrin	Flat	300	1/2"	1 5/8"	0.75	W-5205-EZ-DB-1/2
5"	1 1/4"	BALL	Crown	250	3/8"	1 5/8"	0.75	W-5205-EZC-PB-3/8
5"	1 1/4"	Delrin	Crown	250	1/2"	1 5/8"	0.75	W-5205-EZC-DB-1/2
5"	2"	No Bearing	Flat	375	1 3/16"	2 3/16"	1.04	W-6705-EZ-1 3/16
5"	2"	No Bearing	Crown	300	1 3/16"	2 3/16"	1	W-6705-EZC-1 3/16
5"	2"	Roller	Flat	375	3/4"	2 3/8"	1.36	W-6705-EZ-RB-3/4
5"	2"	Roller	Crown	300	3/4"	2 3/8"	1.32	W-6705-EZC-RB-3/4
5"	2"	BALL	Flat	375	1/2"	2 7/16"	1.36	W-6705-EZ-BB-1/2
5"	2"	BALL	Crown	300	1/2"	2 7/16"	1.32	W-6705-EZC-BB-1/2
5"	2"	Annular Ball	Flat	375	1/2"	2 7/16"	1.36	W-6705-EZ-PBC-1/2
5"	2"	Annular Ball	Crown	300	1/2"	2 7/16"	1.32	W-6705-EZC-PBC-1/2
5"	2"	Flanged Delrin	Flat	375	1/2", 3/4"	2 3/8"	1.12	W-6705-EZ-DB-**
5"	2"	Flanged Delrin	Crown	300	1/2", 3/4"	2 3/8"	1.08	W-6705-EZC-DB-**
5"	2"	Delrin Bushings	Flat	375	1/2", 3/4"	2 3/16"	1.12	W-6705-EZ-DBC-**
5"	2"	Delrin Bushings	Crown	300	1/2", 3/4"	2 3/16"	1.08	W-6705-EZC-DBC-**
6"	1 1/4"	BALL	Flat	300	3/8"	1 5/8"	1	W-5206-EZ-PB-3/8
6"	1 1/4"	Delrin	Flat	300	1/2"	1 5/8"	1	W-5206-EZ-DB-1/2
6"	1 1/4"	BALL	Crown	300	3/8"	1 5/8"	0.75	W-5206-EZC-PB-3/8
6"	1 1/4"	Delrin	Crown	300	1/2"	1 5/8"	0.75	W-5206-EZC-DB-1/2
6"	2"	No Bearing	Flat	600	1 3/16"	2 3/16"	1.3	W-6706-EZ-1 3/16
6"	2"	No Bearing	Crown	450	1 3/16"	2 3/16"	1.3	W-6706-EZC-1 3/16
6"	2"	Roller	Flat	600	3/4"	2 3/8"	1.62	W-6706-EZ-RB-3/4
6"	2"	Roller	Crown	450	3/4"	2 3/8"	1.62	W-6706-EZC-RB-3/4

** - Include Bearing Size

EZ WHEEL®

CAPACITIES UP TO **675 LBS**

Diameter (Ins.)	Tread Width	Bearing Type	Tread Profile	Capacity (LBS)	Bore Size	Hub Length	Wheel Weight (lbs)	Part Number
6"	2"	BALL	Flat	600	1/2"	2 7/16"	1.62	W-6706-EZ-BB-1/2
6"	2"	BALL	Crown	450	1/2"	2 7/16"	1.62	W-6706-EZC-BB-1/2
6"	2"	Annular Ball	Flat	600	1/2"	2 7/16"	1.62	W-6706-EZ-PBC-1/2
6"	2"	Annular Ball	Crown	450	1/2"	2 7/16"	1.62	W-6706-EZC-PBC-1/2
6"	2"	Flanged Delrin	Flat	600	1/2", 3/4"	2 3/8"	1.08	W-6706-EZ-DB-**
6"	2"	Flanged Delrin	Crown	450	1/2", 3/4"	2 3/8"	1.08	W-6706-EZC-DB-**
6"	2"	Delrin Bushing	Flat	600	1/2", 3/4"	2 3/16"	1.08	W-6706-EZ-DBC-**
6"	2"	Delrin Bushing	Crown	450	1/2", 3/4"	2 3/16"	1.08	W-6706-EZC-DBC-**
8"	2"	No Bearing	Flat	675	1 3/16"	2 3/16"	2.12	W-6708-EZ-1 3/16
8"	2"	No Bearing	Crown	500	1 3/16"	2 3/16"	2.12	W-6708-EZC-1 3/16
8"	2"	Roller	Flat	675	3/4"	2 3/8"	2.44	W-6708-EZ-RB-3/4
8"	2"	Roller	Crown	500	3/4"	2 3/8"	2.44	W-6708-EZC-RB-3/4
8"	2"	BALL	Flat	675	1/2"	2 7/16"	2.44	W-6708-EZ-BB-1/2
8"	2"	BALL	Crown	500	1/2"	2 7/16"	2.44	W-6708-EZC-BB-1/2
8"	2"	Annular Ball	Flat	675	1/2"	2 7/16"	2.44	W-6708-EZ-PBC-1/2
8"	2"	Annular Ball	Crown	500	1/2"	2 7/16"	2.44	W-6708-EZC-PBC-1/2
8"	2"	Flanged Delrin	Flat	675	1/2", 3/4"	2 3/8"	2.2	W-6708-EZ-DB-**
8"	2"	Flanged Delrin	Crown	500	1/2", 3/4"	2 3/8"	2.2	W-6708-EZC-DB-**
8"	2"	Delrin Bushing	Flat	675	1/2", 3/4"	2 3/16"	2.2	W-6708-EZ-DBC-**
8"	2"	Delrin Bushing	Crown	500	1/2", 3/4"	2 3/16"	2.2	W-6708-EZC-DBC-**

** - Include Bearing Size