

## DI WHEEL®

CAPACITIES UP TO **15,000 LBS**



Ductile Iron Wheel

OPERATING  
TEMPERATURE: -45F to 800F

### ATTRIBUTES

#### DESCRIPTION:

Extra Thick walled, Heavy Duty Core, Hub and Tread

#### SPECIAL:

- Flat Treads Extra Heavy Load

#### EXCELLENT FOR:

- Floor Protection,
- Deflecting Debris,
- Factory Use,
- Push/Pull Ease,
- Platform & Stock Trucks,
- Outdoor Use and Heavy Loads,
- Smooth, Easy Rolling & Longevity,
- Towline Applications,
- Heavy Material Handling,
- Abusive Applications,
- Ease of Maneuverability,
- Prolonging of Equipment Life

| Diameter (Ins.) | Tread Width | Bore Size | Capacity (LBS) | Hub Length | Wheel Weight (lbs) | Part Number        |
|-----------------|-------------|-----------|----------------|------------|--------------------|--------------------|
| 6"              | 3"          | 1 1/4"    | 15,000         | 3 1/4"     |                    | W-9106-DI-TB-1 1/4 |
| 8"              | 3"          | 1 1/4"    | 10,000         | 3 1/4"     |                    | W-9108-DI-TB-1 1/4 |
| 10"             | 3"          | 1 1/4"    | 10,500         | 3 1/4"     |                    | W-9110-DI-TB-1 1/4 |
| 12"             | 3"          | 1 1/4"    | 10,000         | 3 1/4"     |                    | W-9112-DI-TB-1 1/4 |